

१३४ फिटिङ्सको दर रेट ०७८ / ०७९

S.N	Description Of Items	MRP Per Pcs (EX. VAT)	MRP (Ex. VAT)
1	Bricks Grey Color with compressive strength M10 or above. (Specification: Thickness: 70mm, Dimension: 230 x110x70, Tolerance/others:Machine Made Precast Concrete Bricks)	17	9994
	Bricks Single Color with compressive strength M10 or above. (Specification: Thickness: 70mm, Dimension: 230x110x 70, Tolerance/others:Machine Made Precast Concrete Bricks)	19	1108
2	Bricks Grey Color with compressive strength M 10 or above. (Specification: Thickness: 55mm, Dimension: 230x110x55, Tolerance/others:Machin ^e Made Precast Concrete Bricks)	15	11397
	Bricks Single Color with compressive strength M 10 or above. (Specification: Thickness: 55mm, Dimension: 230x110x 55, Tolerance/others:Machine Made Precast Concrete Bricks)	16	12120
3	Hallocon Grey Color with compressive strength M7 or above. (Specification: Thickness: 200mm, Dimension: 390x200x55, Tolerance/others:Machine Made Precast Concrete Bricks)	118	1602
	Hallocon Single Color with compressive strength M7 or above. (Specification: Thickness: 200mm, Dimension: 390x200x55, Tolerance/others:Machine Made Precast Concrete Bricks)	143	1939
4	Hallocon Grey Color with compressive strength M7 or above. (Specification: Thickness: 150mm, Dimension: 390x150x190, Tolerance/others:Machine Made Precast Concrete Bricks)	93	1265
	Hallocon Single Color with compressive strength M7 or above. (Specification: Thickness: 150mm, Dimension: 390x150x190, Tolerance/others:Machine Made Precast Concrete Bricks)	112	1518
5	Hallocon Grey Color with compressive strength M7 or above. (Specification: Thickness: 100mm, Dimension: 390x100x190, Tolerance/others:Machine Made Precast Concrete Bricks)	81	1096
	Hallocon Single Color with compressive strength M7 or above. (Specification: Thickness: 100mm, Dimension: 390x100x190, Tolerance/others:Machine Made Precast Concrete Bricks)	93	1265
6	Hexagon Interlock Payers Grey Color with compressive strength M35 or above. Thickness: 50mm, Dimension: 226 x200 x50 (NS Standard)	30	918
	Hexagon Interlock Pavers Single Color with compressive strength M35 or Thickness: 50mm, Dimension: 226x200x50 (NS Standard)	37	1113
	Hexagon Interlock Payers Blended Color with compressive strength M35 or above. Thickness: 50mm, Dimension: 226* 200* 50 (NS Standard)	40	1113
	Hexagon Interlock Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension: 226 x200 x60 (NS Stan	36	1076
7	Hexagon Interlock Payers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension: 226* 200* 60 (NS Standard)	42	1271
	Hexagon Interlock Payers Blendede Color with compressive strength M35 or above. Thickness: 60mm, Dimension: 226* 200* 60 (NS Standard)	45	1354
	Hexagon Interlock Pavers Grey Color with compressive strength M40 or above. Thickness: 70mm, Dimension: 226 x200 x70 (NS Stan	44	1317
8	Hexagon Interlock Pavers Single Color with compressive strength M40 or above. Thickness: 70mm, Dimension: 226 x200 x70 (NS Stan	50	1512
	Hexagon Interlock Pavers Blended Color with compressive strength M40 or above. Thickness: 70mm, Dimension: 226 x200 x70 (NS Stan	53	1596
	Hexagon Interlock Pavers Grey Color with compressive strength M40 or above. Thickness: 80mm, Dimension: 226 x200 x80 (NS Stan	53	1596
9	Hexagon Interlock Pavers Single Color with compressive strength M40 or above. Thickness: 80mm, Dimension: 226 x200 x80 (NS Stan	60	1791
	Hexagon Interlock Pavers Blended Color with compressive strength M40 or above. Thickness: 80mm, Dimension: 226 x200 x80 (NS Stan	63	1874
10	Rectangulae Interlock Pavers Grey Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 200x100 x60 (NS Standard)	30	1516
	Rectangulae Interlock Pavers single Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 200x100 x60 (NS Standard)	36	1845
	Rectangulae Interlock Pavers Blended Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 200x100 x60 (NS Standard)	39	1985

१३४ फिटिङ्सको दर रेट ०७८ / ०७९

S.N	Description Of Items	MRP Per Pcs (EX. VAT)	MRP (Ex. VAT)
11	Rectangulae Interlock Pavers Grey Colour with compressive strength M50 or above. Thickness: 100mm, Dimension: 200x100 x100 (NS Standard)	66	3340
	Rectangulae Interlock Pavers single Colour with compressive strength M50 or above. Thickness: 100mm, Dimension: 200x100 x100 (NS Standard)	73	3688
	Rectangulae Interlock Pavers Blended Colour with compressive strength M50 or above. Thickness: 100mm, Dimension: 200x100 x100 (NS Standard)	76	3827
12	Behaton Interlock Pavers Grey Colour with compressive strength M35 or above. Thickness: 50mm, Dimension: 200x165 x50 (NS Standard)	35	1288
	Behaton Interlock Pavers single Colour with compressive strength M35 or above. Thickness: 50mm, Dimension: 200x165 x50 (NS Standard)	41	1529
	Behaton Interlock Pavers blended Colour with compressive strength M35 or above. Thickness: 50mm, Dimension: 200x165 x50 (NS Standard)	44	1633
13	Behaton Interlock Pavers Grey Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 200x165 x80 (NS Standard)	51	1886
	Behaton Interlock Pavers single Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 200x165 x80 (NS Standard)	57	2128
	Behaton Interlock Pavers Blended Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 200x165 x80 (NS Standard)	60	2220
14	Uni Interlock Pavers Grey Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 240x165 x60 (NS Standard)	36	1255
	Uni Interlock Pavers Single Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 240x165 x60 (NS Standard)	42	1483
	Uni Interlock Pavers Blended Colour with compressive strength M35 or above. Thickness: 60mm, Dimension: 240x165 x60 (NS Standard)	45	1580
15	Zigzag Interlock Pavers Grey Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 225x112.5 x80 (NS Standard)	50	2012
	Zigzag Interlock Pavers single Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 225x112.5 x80 (NS Standard)	57	2283
	Zigzag Interlock Pavers blende Colour with compressive strength M40 or above. Thickness: 80mm, Dimension: 225x112.5 x80 (NS Standard)	60	2394
16	Zigzag Interlock Pavers Grey Colour with compressive strength M50 or above. Thickness: 100mm, Dimension: 225x112.5 x100 (NS Standard)	81	3212
	Zigzag Interlock Pavers single Colour with compressive strength M50 or above. Thickness: 100mm, Dimension: 225x112.5 x100 (NS Standard)	89	3546
	Zigzag Interlock Pavers blende Colour with compressive strength M50 or above. Thickness: 80mm, Dimension: 225x112.5 x100 (NS Standard)	93	3680
17	Romba 3D interlock Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*173 *60 (NS Standard)	46	1365
	Rooiba 3D interlock Pavers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*173 *60 (NS Standard)	53	1567
	Romba 3D interlock Pavers Blended Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*173 *60 (NS Standard)	55	1641
18	Square Interlock Pavers Grey Color with compressive strength M35 or Thickness: 60mm, Dimension:200*200*60 (NS Standard)	59	1476
	Square Interlock Pavers Singi COIOR with compressive strength M35 or above. Thickness: 60mm, Dimension:200x200x 60 (HS Standard)	65	1640
	Square Interlock PitYers Blended Color with compressive strength M35 or above. Thickness : 60mm, Dimension:200* 200* 60 (NS Standard)	68	1718
	Cobble Interlock Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension: 100* 100*60 (NS Standard)	13	1375

१३४ फिटिङ्सको दर रेट ०७८ / ०७९

S.N	Description Of Items	MRP Per Pcs (EX. VAT)	MRP (Ex. VAT)
19	Cobble Interlock Pavers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension:100*100*60 (NS Standard)	16	1625
	Cobble Interlock Pavers Blended Color with compressive strength M35 or above. Thickness: 60mm, Dimension: 100*100*60 (NS Standard)	18	1875
20	Interlock Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (NS Standard)	55	1483
	Interlock Pavers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (HS Standard)	61	1649
	Interlock Pavers Blended Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (NS Standard)	64	1724
21	Interlock With Cobble Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (NS Standard)	59	1476
	Interlock With Cobble Pavers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (NS Standard)	65	1640
	Interlock With Cobble Pavers Blended Color with compressive strength M35 or above. Thickness: 60mm, Dimension:200*200*60 (NS Standard)	68	1710
22	Matrix Slab / Tiles Grey Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:400*400*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	183	1148
	Matrix Slab / Tiles Single Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:400*400*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	203	1273
	Matrix Slab / Tiles Blended Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:400*400*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	227	1422
23	Mixed Fusion Slab / Tiles Grey Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:1200*800*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	1102	1150
	Mixed Fusion Slab / Tiles Single Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:1200*800*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	1221	1274
	Mixed Fusion Slab / Tiles Blended Color with compressive strength M35 or above. (Specification: Thickness: 40mm, Dimension:1200*800*40, Tolerance/others: ±1 mm Variance in thickness, Proper Interlock Grooves & Pigment Color, Water absorption <6%)	1378	1439
24	Nostalgic Pavers Grey Color with compressive strength M35 or above. Thickness: 60mm, Dimension:1140x960x60mm/ Pallet (NS Standard)	2500	2403
	Nostalgic Pavers Single Color with compressive strength M35 or above. Thickness: 60mm, Dimension:1140x960x60mm/ Pallet (HS Standard)	2750	2643
	Nostalgic Pavers Blended Color with compressive strength M35 or above. Thickness: 60mm, Dimension:1140x960x60mm/ Pallet (HS Standard)	3000	2883
25	Glass Interlock Pavers Grey Color with compressive strength M40 or above. Thickness: 80mm, Dimension:400x600x80mm (NS Standard)	402	1676
26	Half battard Kerbstone Grey Color with compressive strength M15. Thickness: 200mm, Dimension:300X200X350 (M)	300	999
	Half battard Kerbstone Grey Color with compressive strength M20. Thickness: 200mm, Dimension:300*200*350 (LxH) (NS Standard)	312	1038
	Half battard Kerbstone Grey Color with compressive strength M25. Thickness: 200mm, Dimension:300x200x350 (LxBxH) (HS Standard)	336	1118

१३४ फिटिङ्सको दर रेट ०७८ / ०७९

S.N	Description Of Items	MRP Per Pcs (EX. VAT)	MRP (Ex. VAT)
27	Half battcrd Kerbstone Grey Color with compmssive strength MI 5. ThlCknCS: 165a o ncnsion:300* 165°325 (LnBxH) (NS Standard)	252	839
	Half battcrd Kerbstone Grey Color with compressive strength M20. Thicimess/ Breadth 165nim, DitT1gItsiOn:300x 165x325 (LxBxH) (NS Standard)	276	919
	Half battcrd Kerbstone Grey Color with compressive strength M25. Thickness/ Breadth: 165mm, Dimension: 300x 165x325 (LxBxH) (NS Standard)	300	999
28	Half battcrd KerbStone Grey Color with compressive strength MIS. TbfCknCSS: 200mm, Dimension: 250•200•380 (LxBxH)	300	1200
	Half battcrd Kerbstone Grey Color with compressive strength M20. Thickness: 200mm, Dimension: 250•200•380 (LxBxH) (NS Standard)	312	1248
	Half battcrd Kerbstone Grey Color with compressive strength M25. Thickness: 200mm, Dimension: 250*200*380 (LxBxH) (NS Standard)	336	1344
29	Bullnose Kerbstone Grey Color with compressive strength M15. Thickness: 200mm, Dimension:300•200•350 (LxBxH)	342	1138
	Bullnose Kerbstone Grey Color with compressive strength M20. Thicluiess: 200mm, Dimension:300•200•350 (LxBxH) (NS Standard)	372	1238
	Bullnose Kerbstone Grey Color with compressive strength M25. Thickness: 200mm, Dimension:300•200•350 (LxBxH) (this Standard)	390	1298
30	V Shape Drain MOU & female set with compressive strength M35. Thickness: 70inin, Dimension: 300x75x499.5 (LxBxH)	388	1294

ACC BLOKS

S.N	Description of Goods	Quantity	Rate Per CBM
			Rates
1.0	600X200X200 (0.024 CBM/block)	1 CBM	11060
2.0	600X200X150 (0.018 CBM/block)	1 CBM	11060
3.0	600X200X100 (0.018 CBM/block)	1 CBM	11060

[illegible]

[illegible]

Units
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
SQM
RM
RM
RM

Units
RM
RM
RM
RM
RM
RM
RM
RM
RM
RM

Rate per pcs
Exclusi ve 13% VAT
265
199
132